



Part Number	Size Usage Range			Maximum Allowable Back Pressure			Product Weight	Deflated Length	Deflated Diameter	Bypass Size	Inflation Valve	Eyebolt(s)
	Nominal Size	Minimum Diameter	Maximum Diameter	Air* Pressure	Head Pressure	Required Inflation Pressure						
Single Size Muni Ball® Plugs												
262 008	1 1/2" (40mm)	1.49" (38mm)	1.88" (48mm)	22 psi (1.5bar)	50 ft (15M)	40 psi (2.8bar)	.3 lbs (.2kg)	3.8" (97mm)	1.4" (36mm)	1/8"	NR**	NA
262 010	2" (50mm)	1.88" (48mm)	2.25" (57mm)	22 psi (1.5bar)	50 ft (15M)	40 psi (2.8bar)	.4 lbs (.3kg)	6.00" (152mm)	1.75" (44mm)	1/8"	NR	NA
262 021	3" (75mm)	2.62" (67mm)	3.25" (83mm)	22 psi (1.5bar)	50 ft (15M)	40 psi (2.8bar)	1.25 lbs (.5kg)	8.00" (203mm)	2.50" (64mm)	3/4"	NR	NA
262 048	4" (100mm)	3.25" (83mm)	4.25" (108mm)	22 psi (1.5bar)	50 ft (15M)	40 psi (2.8bar)	1.5 lbs (.7kg)	8.00" (203mm)	3.13" (80mm)	3/4"	NR	1/4" (1)
262 064	6" (150mm)	4.5" (114mm)	6.25" (159mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	2 lbs (1kg)	7.00" (178mm)	4.40" (112mm)	1 1/2"	1/8"	1/4" (1)
262 080	8" (200mm)	7" (178mm)	8.25" (210mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	5 lbs (2.3kg)	10.00" (254mm)	6.71" (170mm)	3"	1/4"	3/8" (1)
262 110	10" (250mm)	9" (229mm)	10.25" (260mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	9 lbs (4kg)	11.75" (298mm)	8.75" (222mm)	3"	1/4"	3/8" (1)
262 129	12" (300mm)	10.5" (267mm)	12.25" (311mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	13 lbs (6kg)	13.75" (350mm)	10.25" (260mm)	3"	1/4"	3/8" (1)
262 137	15"-16" (375-400mm)	14" (356mm)	16.25" (413mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	33 lbs (15kg)	19.75" (502mm)	13.62" (346mm)	3"	1/4"	3/8" (2)
262 188	18" (450mm)	17.5" (445mm)	19.85" (504mm)	13 psi (.9bar)	30 ft (9.1M)	25 psi (1.7bar)	79 lbs (36kg)	24.75" (629mm)	16.90" (429mm)	4"	1/4"	1/2" (2)
262 218	21" (525mm)	18.85" (479mm)	21.38" (543mm)	13 psi (.9bar)	30 ft (9.1M)	25 psi (1.7bar)	87 lbs (39.2kg)	26.00" (660mm)	18.20" (462mm)	4"	1/4"	1/2" (2)
262 242	24"	21.95"	24.9"	13 psi	30 ft	25 psi	124 lbs	28.75"	21.19"	4"	1/4"	1/2" (2)

	(600mm)	(558mm)	(632mm)	(.9bar)	(9.1M)	(1.7bar)	(56.2kg)	(730mm)	(538mm)			
Multi Size Muni Ball® Plugs												
265 048	4"-6" (100-150mm)	3.75" (95mm)	6.25" (158mm)	17 psi (1.2bar)	40 ft (12M)	35 psi (2.4bar)	2 lbs (1kg)	10.75" (273mm)	3.48" (88mm)	3/4"	1/8"	1/4" (1)
265 068	6"-8" (150-200mm)	4.75" (121mm)	8.25" (210mm)	17 psi (1.2bar)	40 ft (12M)	35 psi (2.4bar)	2 lbs (1kg)	13.0" (330mm)	4.50" (114mm)	1 1/2"	1/4"	3/8" (1)
265 071	8"-10" (200-250mm)	7" (178mm)	10.25" (260mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	7 lbs (3kg)	16.0" (406mm)	6.75" (171mm)	2"	1/4"	3/8" (1)
265 098	8"-12" (200-300mm)	7" (178mm)	12.25" (311mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	7 lbs (3kg)	22.0" (559mm)	6.75" (171mm)	2"	1/4"	3/8" (1)
265 128	12"-18" (300-450mm)	10.75" (273mm)	18.8" (477mm)	13 psi (.9bar)	30 ft (9.1M)	25 psi (1.7bar)	32 lbs (14.5kg)	27.25" (692mm)	10.50" (267mm)	4"	1/4"	3/8" (2)

***Always block plugs when conducting air tests!**

** Not Removable