

Part Number	Nominal Size	Size Usage Range			Maximum Allowable Back Pressure			Required Inflation Pressure	Product Weight	Deflated Length	Deflated Diameter	Inflation Valve Thread Size	Carton Quantity
		Minimum Diameter	Maximum Diameter	Maximum Back Pressure	Air Pressure	Head Pressure							
<b>Single Size Test Ball® Plugs</b>													
270 008	.75" - 1.25" (20-30mm)	.75" (19mm)	1.31" (33mm)	17 psi (1.2bar0)	40 ft (12M)	45 psi (3.1bar)	4.0 oz (0.1kg)	3.75" (95mm)	.73" (18.5mm)	Molded in Valve w/ Cap	6		
270 016	1.25"-1.50" (30-40mm)	1.17" (30mm)	1.75" (44mm)	13 psi (.9bar)	30 ft (9.1M)	40 psi (2.8bar)	3.5 oz. (0.1kg)	5.56" (141mm)	1.12" (33mm)	Molded in Valve w/Cap	6		
270 024	2.0" (50mm)	1.90" (48mm)	2.25" (57mm)	13 psi (.9bar)	30 ft (9.1M)	40 psi (2.8bar)	3.5 oz. (0.1kg)	3.34" (85mm)	1.78" (45mm)	Molded in Valve w/Cap	6		
270 108	2.5" (65mm)	2.34" (60mm)	2.75" (70mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	6.5 oz (0.20kg)	2.31 (58.5mm)	4.50" (114mm)	Molded in Valve w/Cap	1		
270 032	3.0" (75mm)	2.77" (70mm)	3.25" (83mm)	13 psi (.9bar)	30 ft (9.1M)	35 psi (2.4bar)	6.5 oz (0.20kg)	5.18" (132mm)	2.64" (67mm)	Molded in Valve w/Cap	6		
270 040	4.0" (100mm)	3.41" (87mm)	4.25" (108mm)	13 psi (.9bar)	30 ft (9.1M)	30 psi (2.1bar)	9.0 oz (0.25kg)	6.41" (163mm)	3.28" (83mm)	Molded in Valve w/Cap	6		
270 059	5.0" (125mm)	4.60" (117mm)	5.25" (133mm)	13 psi (.9bar)	30 ft (9.1M)	30 psi (2.1bar)	1.3 lbs (0.6kg)	7.88" (200mm)	4.48" (114mm)	Molded in Valve w/Cap	1		
270 067	6.0" (150mm)	5.44" (138mm)	6.25" (159mm)	13 psi (.9bar)	30 ft (9.1M)	30 psi (2.1bar)	1.9 lbs (0.85kg)	9.05" (230mm)	5.32" (135mm)	Molded in Valve w/Cap	1		
041 386	8.0" (200mm)	7.0" (178mm)	8.25" (210mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	3.4lbs (1.6kg)	10.11" (257mm)	6.75" (172mm)	1/4" (Removable)	1		
041 394	10.0" (250mm)	9.0" (229mm)	10.25" (260mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	5.6 lbs (2.5kg)	11.74" (298mm)	8.7" (221mm)	1/4" (Removable)	1		
041 408	12.0" (300mm)	10.5" (267mm)	12.25" (311mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	10.94 lbs	13.83" (351mm)	10.30" (262mm)	1/4" (Removable)	1		

Multi Size Test Ball® Plugs											
									(5kg)		
275 058	6.0"-8.0" (150- 200mm)	4.75" (121mm)	8.25" (210mm)	17 psi (1.2bar)	40 ft (12M)	35 psi (2.4bar)	2.2 lbs (1.02kg)	13.0" (330mm)	4.50" (114mm)	1/4" (Removable)	1
275 085	8.0"-12.0" (200- 300mm)	7.0" (178mm)	12.25" (311mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	6.63 lbs (3kg)	16.0" (406mm)	6.75" (171mm)	1/4" (Removable)	1
275 128	12.0"-18.0" (300- 450mm)	10.75" (273mm)	18.25" (464mm)	17 psi (1.2bar)	40 ft (12M)	25 psi (1.7bar)	22.4 lbs (10.2kg)	24.0" (610mm)	10.50" (267mm)	1/4" (Removable)	1