



Theoretical Coverage in Square Feet per U.S. Gallon

		Required Dry Film Thickness per Coat (mils)																								
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16									
100	1604	802	535	401	321	267	229	201	178	160	146	135	123	115	107	100	Theoretical Coverage per Gallon									
95	1524	762	511	381	305	254	218	191	169	152	139	127	117	109	102	95										
90	1444	722	481	361	289	241	206	181	160	144	131	120	111	104	96	90										
85	1363	682	455	341	273	227	195	170	152	136	124	114	105	98	91	85										
80	1283	642	428	321	257	214	183	160	143	128	117	107	98	92	86	80										
75	1203	602	401	301	241	201	172	150	134	120	109	100	92	86	80	75										
70	1123	561	374	281	225	187	160	140	125	112	102	94	86	80	75	70										
65	1043	521	348	261	209	174	149	130	116	104	95	87	80	75	70	65										
60	962	481	321	241	193	160	138	120	107	96	88	80	74	69	64	60										
55	882	441	294	221	176	147	126	110	98	88	80	74	68	63	59	55										
50	802	401	267	201	160	134	115	100	89	80	73	67	62	58	54	50										
45	772	361	241	181	144	120	103	90	80	72	66	60	55	52	48	45										
40	642	321	214	160	128	107	92	80	71	64	58	54	49	46	43	40										
35	561	281	187	140	112	94	80	70	62	56	51	47	43	40	37	35										
30	481	241	160	120	96	80	69	60	54	48	44	40	37	35	32	30										
25	401	201	134	100	80	67	57	50	45	40	37	33	31	29	27	25										

Solids Content by Volume (%)

*Subtract 25% from above figure to achieve actual (practical) coverage. This allows for material loss due to wind or other conditions.

Pipeline Supply and Service Co., Inc. • Houston, TX 77054
Phone 713-747-0090 • Fax 713-747-0855
<http://www.pipelinesupply.com/>